

200



11 11 139 135



€ Eagle

099

TiTAN





**Designed for rugged retail and industrial applications** Weighing | Counting | Accumulation | Liter Conversion













### Model & Range Chart :

| Model No. | Capacity | Division | Pan Size     | Display | MOC Housing | MOC Pan    |
|-----------|----------|----------|--------------|---------|-------------|------------|
| TITAN-E   | 5/7.5 kg | 0.5/1 g  | 250 x 195 mm | LED     | ABS Plastic | SS 304 Pan |
| TITAN-E   | 10 kg    | 1 g      |              |         |             |            |
| TITAN-E   | 10/20 kg | 1/2 g    |              |         |             |            |
| TITAN-E   | 20/30 kg | 2/5 g    |              |         |             |            |


## **Standard Features:**

- Light and compact table top weighing scale
- ABS cabinet
- SS 304 pan
- Level adjustable legs
- Spirit level indicator near the pan
- Lithium-ion battery operated
- RS232 port
- Power adaptor 5 V, 1 A, with type C USB charging connector
- Big rear display equivalent to front display
- Weighing, piece counting, accumulation, litre conversion modes
- Provision to connect with portable thermal printer

## **OPTIONAL:**

- 1) Portable 2 inch thermal receipt printer
- 2) Portable 2 inch thermal label printer

## **Print Format:**



(Accumulation Weighing)

\*Models and specifications are subject to change without any prior notification.

# **Technical Specification:**

| Description                | Titan Table Top Weighing Scale                                       |  |  |  |
|----------------------------|--|--|--|--|
| Physical dimension         | 256.5 x 266.5 x 121 mm   |  |  |  |
| Net weight                 | 2.4 kg approx  |  |  |  |
| Weight sensor              | Aluminium loadcell   |  |  |  |
| Processor                  | STM 32 BIT ARM   |  |  |  |
| Key board                  | 5 keys   |  |  |  |
| Display type               | LED  |  |  |  |
| No. of displays            | Dual display (Front & Back)  |  |  |  |
| Display size               | LED - with 25 mm digit height  |  |  |  |
| Calibation method          | External calibration firmware based                                  |  |  |  |
| Power adaptor              | USB C Type<br>O/P : 5 V DC, 1 A<br>I/P : 100 V to 230 V AC, 47-63 Hz |  |  |  |
| Power adaptor cable length | 2.5 meter  |  |  |  |
| Operating temp.            | O°C to 50°C  |  |  |  |
| Battery capacity           | Lithium ion, 7.4 V, 1200 mAh   |  |  |  |
| Battery backup             | Estimated time : 8-10 hrs (If the battery is fully charged)          |  |  |  |
| Communication interface    | RS232  |  |  |  |
| RTC                        | Not available  |  |  |  |

## **Features Gallery:**









Level indicator

Heavy duty pan holder with Insect protection covers

Also available in LCD display variant

Adaptor, with type C USB charging connector

. -**ESLEEP** 

LED rear display



Designed, Developed & Manufactured By:

### E. G. Kantawalla Private Limited

Next To Prakash Memorial School, Upper Kharadi Road, Ubale Nagar, Wagholi, Pune-412207

#### **Toll Free Numbers:**

Sales - 1800 - 12 - EAGLE (32453) Service -1860 - 12 - EAGLE (32453) website: www.eaglescales.in

E-mail: sales@egkantawalla.com website: www.egkantawalla.com

Name & Address of Dealer: